

TQ19-51AC

19.5" Intel® Celeron®/Core™ Processor
Industrial Panel PC



Features:

- Support Intel® Celeron®/Core™ i(6/7th Gen) series processor
- Industrial-grade 19.5" widescreen display with PCAP multi-touch
- Support 4*USB+6*COM
- Dual Gigabit Ethernet ports(Intel® I211-AT)
- Fanless design
- IP65-rated front panel
- Optional wide input voltage range 9~36v

Specifications:

System Hardware

CPU	Support Intel® J1900/3855U/3865U/Core™ i (6/7 th Gen.) series processor	Storage	Up to 512GB
Memory	Up to 8GB	Watchdog	0-255 Seconds, setup by software

Display

LCD Type	19.5" TFT-LCD	Viewing Angle	170°(H)*160°(V)
Max. Resoluion	1440*900	Contrast Ratio	1000: 1
Luminance	250 cd/m ²	Backlight Life-Time	50000 hr.(min.)

Touchscreen

Touchscreen Type	Multi-point capacitive touch screen	Hardness	6H
Light Transmission	>85%		

OS

os	Windows 7、Windows 10、Linux
----	----------------------------

I/O Ports

USB	3*USB 2.0 + 1*USB3.0 (Celeron® J1900) 4*USB 3.0 (3855U/3865U/Core™ i(6/7th Gen))	Audio	1*Line-out, 1*Mic-in
Serial port	6*RS232(1*RS422/RS485 optional)	Video	1*HD, 1*VGA
LAN	2* RJ45 Gigabit Ethernet (Intel® I211-AT)	GPIO	4In/4Out
		Expansion Slot	1*Mini PCIe(Wifi/BT/3G/4G optional)

Power

Power Input 9~24V DC Input(9~36V DC optional), 12V/5A power adapter

Environment

Operating Temp. -10°C~60°C, with air flow

Shock Protection acceleration 10g/11ms

Storage Temp. -20°C~70°C

Vibration Protection 5-19Hz/1.0mm amplitude; 19-200Hz/1.0g

Humidity 95% @40°C, non-condensing

acceleration

IP Rating Front panel IP65

Mechanical

Dimension (WxHxD) 472.2*319.2*53.3mm

Mounting VESA mounting: 75*75mm, 100*100mm

Weight 4.48kg

Panel mounting: 462*309mm

Color Silver

Dimensions:

